

WHISPER

Ultrasonic Leak Detector



NOT EVEN A MURMUR WILL ESCAPE DETECTION

INFICON Whisper Ultrasonic Leak Detector is ideal for detecting and locating sources of ultrasonic sound through the use of sophisticated electronic circuitry. Unaffected by audible noise, Whisper incorporates an Internal Noise Control allowing for use in extremely noisy environments, such as mechanical rooms, and around operating chillers. Because Whisper is designed to detect ultrasound at 40.5 kHz, not even a murmur will escape detection.

Use the optional transmitter for quick and accurate leak checking in walk-in coolers / freezers, wall and ceiling joints, around doors, windows, ducts, etc.

APPLICATIONS AT A GLANCE

- ◆ Refrigerant Leaks
- ◆ Locating Worn Bearings
- ◆ Leaks in Pneumatic Control Systems
- ◆ Leaks in Natural Gas, LPG Leaks
- ◆ Leaks in Compressed Air Systems
- ◆ Leaks in Vacuum Systems
- ◆ Butane / Propane Storage Tank Leaks
- ◆ Line Set Leaks in Foundations / Walls
- ◆ Diagnosing Solenoid Operations
- ◆ Steam Traps
- ◆ Electrical Arcing

SPECIFICATIONS

Base unit includes	9 V battery, rubber probe extension, headphones and storage case.
Controls	On / Off switch Sensitivity: maximum / minimum knob
Power	One 9 volt alkaline battery
Weight with battery	9 oz (0.25 kg)
Operating temperature range	32°F to +122°F; 0°C to +50°C
Storage Temperature	14°F to +140°F; -10°C to +60°C
Warranty	2 years

ORDERING INFORMATION

Whisper Ultrasonic Leak Detector	711-202-G1
Transmitter	711-600-G1
Headphones	032-404
Storage case	711-701-G1

Call 1.800.344.3304 for your nearest distributor.



GLOBAL HEADQUARTERS:

Two Technology Place, East Syracuse, NY 13057 USA
Tel: +315.434.1100 Fax: +315.437.3803 E-mail: reachus@inficon.com

Due to INFICON's continuing program of product improvements, specifications are subject to change without notice.
Visit our website for contact information and other sales offices worldwide. www.inficon.com
eibb05a1 (0008)STL ©2001 INFICON Inc.